

KENT INDUSTRIAL (USA) INC.

SGS-2060AHD



- 20" x 60" working capacity
- 3-axis automatic movement with incremental downfeed, electronic auto-crossfeed, and hydraulic powered table movement
- Precision hand scrapped turcrite V and flat table ways and double V column ways for smooth and long lasting precision
- High column design with 23" spindle center to table for extra clearance under the wheel and rapid elevation motor for quick/easy positioning
- Centralized automatic one-shot lubrication system provides lubrication to all points
- Safety 24V control circuit power

PRICE INCLUDES:

19.6" x 59" electric magnetic chuck and control with automatic demagnetizer, Paper filter and magnetic separator coolant system, Overhead parallel dresser, and FREE start up installation service

OPTIONS AND ACCESSORIES:

Acu-Rite 200S DRO (2-axis, 22"x20", 0.0001" res)
DRO installation charge
Static wheel balancing base
Extra wheel flange
Rustlick coolant (1 gal, mixes 1:30)

GENERAL SPECIFICATIONS:

Table travel:	65"	Grinding wheel:	16"x2"x5"
Saddle travel:	21.6"	Vertical graduation:	0.0001"
Working capacity:	19.6"x59.1"	Vertical revolution:	0.0200"
T-slot:	3 x 9/16"	Auto downfeed increment:	0.0002" 10 steps
Spindle motor:	10 HP	Spindle center to table:	23.6"
Spindle speed:	1750 RPM	Machine weight Net/Gross:	11,800/13,200 LBS

STANDARD ACCESSORIES:

Grinding wheel, Wheel flange, Wheel balancing base, Wheel balancing arbor, Diamond table dresser base and tip, Leveling bolts and pads, Work light, Toolbox with tools.
