

## Roll-In Saw's Model TF1420 Provides Tilt-Frame Versatility for all Types of Jobs

A vertical bandsaw that combines large capacity with versatility – and can accommodate small and large work in nominal settings as well as at variable angles (0 to 45°) left or right: the TF1420 can't be beat.

Roll-In's Tilt Frame Bandsaw can do all the operations our EF1459 Model can do, plus offering the advantage of mitering simply by tilting the frame without having to remove the work.

The TF1420 has the power, speed control, and feed pressure required to ensure maximum accuracy and efficiency. This saw requires no extra training to master. It is easier to operate, equal to any task, and is less expensive than the comparable saws in its class.



Simple to operate, the TF1420 is a rugged machine built for many trouble-free years of service.

### Technical Data

Capacity Under Guides	20" Under guides @ 90°
Throat	14" Throat 14" x 13" @ 45°
Blade Travel	14" into work
Blade Size	1"Width x 12'11"Length .035 Thick (bi-metal)
Blade Guards	Blade guard moves up and down with guide bar to ensure operator safety when cutting
Blade Speeds	70 to 400 sfpm digital speed control with LCD readout
Table	Precision ground 31 1/2" x 25 1/2"
Table Height	37" from floor
Feed System	Infinitely adjustable air over hydraulic cylinder for feed control from 0 to 175 lbs.
Wheels	14" Cast iron wheels
Motor	2HP 220/440V three-phase (TEFC)
Dimensions	60"W x 80"H x 80"L
Shipping Weight	1,320 lbs. F.O.B. Cleveland, Ohio

### Special Features

Quick action vise (can be moved to either side)
Blade cleaning brush
Coolant - blade misting system

(Specifications subject to change without notice)  
One Year Limited Warranty